



## BU-2010-VFIR-M5X

**2 MP OUTDOOR BULLET, 5X, POE, H.264/H.265, IP66, IR 60 MTS, P2P, ONVIF 2.4**

### Technical Specifications

#### Camera

<b>Image sensor</b>	IMX323 CMOS Sensor
<b>Resolution</b>	1080P
<b>Effective Pixels</b>	1985(H)*1105(V)
<b>TV System</b>	PAL/NTSC
<b>Electronic Shutter Time</b>	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec
<b>Sync System</b>	External
<b>Usable Illumination</b>	0.01Lux
<b>S/N Ratio</b>	≥52dB
<b>Scanning System</b>	Progressive
<b>Video Output</b>	Network

#### Lens

<b>Focus Length</b>	2.7-13.5mm 5X Motor Zoom Auto Focus Lens
<b>Focus Control</b>	Auto
<b>Lens Type</b>	Motorized
<b>Pixels</b>	2M Pixels

#### Night Vision

<b>Infrared LED</b>	42μ x 6PCS
<b>Infrared Distance</b>	60M
<b>IR Status</b>	Under 10 Lux By CDS
<b>IR Power On</b>	CDS Auto Control

#### Camera Features

<b>Day/Night</b>	Color/ B&W (IR-CUT )
<b>Compression</b>	H.264/H.264+/H.265/H.265+/JPEG/AVI /MIPEG
<b>Image settings</b>	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR, White Balance, BLC, FLK(Flicker Control)
<b>Privacy Masking</b>	3 Rectangular Zone
<b>WDR</b>	Support
<b>Motion Detection</b>	Support
<b>Recording Mode</b>	NVR/NAS/CMS/Web
<b>Language</b>	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian

#### Package content

- 1 BU-2010-VFIR-M5X camera
- Installation manual and CD

### Main Features

- IMX323 CMOS Sensor
- H.264/H.265 Compression Method
- 2.7-13.5mm 5X Motor Zoom Auto Focus Lens
- IR Distance 60m Max.
- IP66 Outdoor Metal Case



### Network

<b>Ethernet Protocol</b>	RJ-45 (10/100Base-T) TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP, DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP Support ONVIF 2.4
<b>ONVIF</b>	Support ONVIF 2.4
<b>P2P</b>	YES, Support QR Code
<b>POE</b>	Optional, Support IEEE 802.3af
<b>WIFI</b>	N/A
<b>Main Stream</b>	1920*1080@30fps
<b>Sub Stream</b>	720*480@30fps
<b>IE Brower</b>	IE8-11, Firefox
<b>Smart Phone</b>	iPhone, iPad, Android, Android Pad

### General

<b>Housing</b>	Metal , IP66
<b>Anti-cut Bracket</b>	Yes
<b>IR Cut Filter</b>	Yes
<b>Operation Temperature</b>	-10°C ~ +50°C RH95% Max
<b>Storage Temperature</b>	-20°C ~ +60°C RH95% Max
<b>Power Source</b>	DC12V±10%, 1150mA
<b>Dimension</b>	312(W) x 133(H) x102(D)mm
<b>Weight</b>	1800g