



H.265

BUS-5030-VF

**5 MP BULLET,
VARIFOCAL, POE, IP66,
IR 60 MTS, P2P, ONVIF 2.4**

Technical Specifications

Camera

Image sensor	IMX176
Resolution	5MP
Effective Pixels	2592(H)*1944(V)
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/1-1/10000Sec; NTSC 1/1-1/10000Sec
Sync System	Internal
Usable Illumination	0.01Lux
S/N Ratio	≥52dB
Scanning System	Progressive
Video Output	Network

Lens

Focus Length	2.8-12mm
Focus Control	Manual
Lens Type	Manual
Pixels	5M Pixels

Night Vision

Infrared LED	42μ x 6 PCS
Infrared Distance	60M
IR Status	Under 10 Lux By CDS
IR Power On	CDS Auto Control

Camera Features

Day/Night	Color/ B&W (IR-CUT)
Compression	H.264/H.265/JPEG,Support record AVI format
Image settings	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, BLC, FLK(Flicker Control)
Privacy Masking	3 Rectangular Zone
WDR	Yes
Recording Mode	NVR/NAS/CMS/Web
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian

Package content

- 1 cámara BUS-5030-VF
- Installation manual and CD

Main Features

- 1/1,8" Low Illumination CMOS Sensor
- H.264/H.264+/H.265 Compression Method
- 2.8-12mm Varifocal Lens
- IR Distance 60m Max.
- IP66 Outdoor Metal Case



Network

Ethernet Protocol	RJ-45 (10/100Base-T) IPv4, HTTP, TCP/IP, FTP, NTP, RTSP, UDP, SMTP, DNS, DDNS
ONVIF	Support ONVIF 2.4
P2P	YES, Support QR Code
POE	Optional, Support IEEE 802.3af
WIFI	N/A
Main Stream	2592(H)*1944(V)@30fps
Sub Stream	720P x 480P@30fps
IE Brower	IE8-11, Firefox , Chrome
Smart Phone	iPhone, iPad, Android, Android Pad

General

Housing	Weatherproof , IP66
Anti-cut Bracket	Yes
IR Cut Filter	Yes
Operation Temperature	-10°C ~ +50°C RH95% Max
Storage Temperature	-20°C~ +60°C RH95% Max
Power Source	DC12V±10%, 700mA
Dimension	275(W)x90.5(H)x79.5(D)mm
Weight	1.4kgs