



H.265

BUX-4030-B

**4 MP MINI BULLET,
3.6MM, POE, IP66, IR,
H.265,P2P, ONVIF 2.4**

Technical Specifications

Camera

Image sensor	DV4689
Resolution	4MP
Effective Pixels	2688(H)*1520(V)
TV System	PAL/NTSC
Electronic Shutter Time	PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec;
Sync System	External
Usable Illumination	0.01Lux
S/N Ratio	≥52dB
Scanning System	Progressive
Video Output	Network (10/100 Base-T)

Lens

Focus Length	3.6mm/ F2,0
Focus Control	Fixed
Lens Type	Fixed
Pixels	4M Pixels

Night Vision

Infrared LED	Ç 5X24PCS
Infrared Distance	20M
IR Status	Under 10 Lux By CDS
IR Power On	CDS Auto Control

Camera Features

Day/Night	Color/ B&W (IR-CUT)
Compression	H.264/H.264+/H.265+PEG, Support record AVI format.
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, BLC, FLK(Flicker Control)
Privacy Masking	3 Rectangular Zone
Recording Mode	NVR/NAS/CMS/Web
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian

Package content

- 1 BUX-4030 camera
- Installation manual and CD

Main Features

- 1/2.7" Low Illumination CMOS Sensor
- H.264/H.264+/H.265 Compression Method
- 3.6mm Fixed Lens
- IR Distance 20m Max.
- IP66 Outdoor Metal Case



Network

Ethernet Protocol	RJ-45 (10/100Base-T) IPv4, HTTP, TCP/IP, FTP, NTP, RTSP, UDP, SMTP, DNS, DDNS
ONVIF P2P POE WIFI	Support ONVIF 2.4 YES, Support QR Code Optional, Support IEEE 802.3af N/A
Main Stream Sub Stream IE Brower Smart Phone	2560X1440@30fps 720X480@30fps IE8-11, Chrome iPhone, iPad, Android, Android Pad

General

Housing Anti-cut Bracket IR Cut Filter Operation Temperature Storage Temperature Power Source Dimension Weight	Weatherproof , IP66 Yes Yes -10°C ~ +50°C RH95% Max -20°C ~ +60°C RH95% Max DC12V±10%, 700mA 148(W)x65(H)x63(D)mm 500g
---	---