



MDX-1330-B

**1.3 MP DOMO, 1080P,
3.6MM, POE, IR,
P2P, ONVIF 2.4**

Technical Specifications

Camera

Image sensor	FH8330
Resolution	1080P
Effective Pixels	1920(H)*1080(V)
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/1-1/10000Sec; NTSC 1/1-1/10000Sec
Sync System	Internal
Usable Illumination	0.01Lux
S/N Ratio	≥52dB
Scanning System	Progressive
Video Output	Network , RJ45

Lens

Focus Length	Board Lens 3.6mm/F2.0
Focus Control	Fixed
Lens Type	Fixed
Pixels	2M Pixels

Night Vision

Infrared LED	Ç 5X24PCS
Infrared Distance	20M
IR Status	Under 10 Lux By CDS
IR Power On	CDS Auto Control

Camera Features

Day/Night	Color/ B&W (IR-CUT)
Compression	H.264/JH.264/+PEG,Support record AVI format.
Image settings	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, BLC, FLK(Flicker Control)
Privacy Masking	3 Rectangular Zone
WDR	YES
Recording Mode	NVR/NAS/CMS/Web
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian

Package content

- 1 MDX-1330-B camera
- Installation manual and CD

Main Features

- 1/2,7" CMOS Sensor
- H.264/H.264+ Compression Method
- 3.6mm Fixed Lens
- IR Distance 20m Max.



Network

Ethernet Protocol	RJ-45 (10/100Base-T) IPv4, HTTP, TCP/IP, FTP, NTP, RTSP, UDP, SMTP, DNS, DDNS
ONVIF	Support ONVIF 2.4
P2P	YES, Support QR Code
POE	Optional, Support IEEE 802.3af
WIFI	N/A
Main Stream	1920(H)*1080(V)@30fps
Sub Stream	720*480@30fps
IE Brower	IE8-11, Firefox
Smart Phone	iPhone, iPad, Android, Android Pad

General

Housing	Metal (IP65)
Lens Angle Adjustment	No, Without Bracket
IR Cut Filter	Yes
Operation Temperature	-10°C ~ +50°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%, 700mA
Dimension	Ç 94,5 x 76(H) mm
Weight	450g