



## MDX-4030-B

**4 MP DOMO,  
H.264/H.265,3.6MM,  
POE,IR,P2P, ONVIF 2.4**

**H.265**

### Technical Specifications

#### Camera

Image sensor	DV4689
Resolution	4MP
Effective Pixels	2688(H)*1520(V)
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec
Reset Button	Optional
Usable Illumination	0.01Lux
S/N Ratio	≥52dB
Scanning System	Progressive
Video Output	Network , RJ45

#### Lens

Focus Length	Board Lens 3.6mm/ F2,0
Focus Control	Fixed
Lens Type	Fixed
Pixels	4M Pixels

#### Night Vision

Infrared LED	Ç 5X24PCS
Infrared Distance	20M
IR Status	Under 10 Lux By CDS
IR Power On	CDS Auto Control

#### Camera Features

Day/Night	Color/ B&W (IR-CUT )
Compression	H.264/H.265/JPEG/AVI/MJPEG
Image settings	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, BLC, FLK(Flicker Control)
Privacy Masking	3 Rectangular Zone
SD Card	Optional
Recording Mode	NVR/NAS/CMS/Web
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian

#### Package content

- 1 MDX-4030-B camera
- Installation manual and CD

### Main Features

- 1/2.8" SONY CMOS Sensor.
- H.264/H.265 Compression Method.
- 3.6mm Fixed Lens.
- IR Distance 20m Max.
- SD Card (optional)



### Network

<b>Ethernet Protocol</b>	RJ-45 (10/100Base-T) TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP, DNS,DDNS,RTSP,RTCP,NTP,SMTP
<b>ONVIF</b>	Support ONVIF 2.4
<b>P2P</b>	YES, Support QR Code
<b>POE</b>	Optional, Support IEEE 802.3af
<b>WIFI</b>	N/A
<b>Main Stream</b>	2560*1440@20fps, 1920*1080@30fps
<b>Sub Stream</b>	720*480@30fps
<b>IE Brower</b>	IE8-11, Chrome
<b>Smart Phone</b>	iPhone, iPad, Android, Android Pad

### General

<b>Housing</b>	Metal (IP65)
<b>Anti-cut Bracket</b>	No
<b>IR Cut Filter</b>	Yes
<b>Operation Temperature</b>	-20°C ~ +60°C RH95% Max
<b>Storage Temperature</b>	-20°C ~ +60°C RH95% Max
<b>Power Source</b>	DC12V±10%, 850 mA
<b>Dimension</b>	Ç 94.5 x 76(H) mm
<b>Weight</b>	450g