



H.265

MDX-5030-B

**5 MP DOMO,
H.264/H.265, 3.6MM,
POE, IR, P2P, ONVIF 2.4**

Technical Specifications

Camera

Image sensor	IMX178
Resolution	5MP
Effective Pixels	2592H)*1944(V)
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec
Reset Button	Optional
Usable Illumination	0.01Lux
S/N Ratio	≥52dB
Scanning System	Progressive
Video Output	Network , RJ45

Lens

Focus Length	Board Lens 3.6mm/ F2,0
Focus Control	Fixed
Lens Type	Fixed
Pixels	5M Pixels

Night Vision

Infrared LED	Ç 5X24PCS
Infrared Distance	20M
IR Status	Under 10 Lux By CDS
IR Power On	CDS Auto Control

Camera Features

Day/Night	Color/ B&W (IR-CUT)
Compression	H.264/H.265/JPEG/AVI/MJPEG
Image settings	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, BLC, FLK(Flicker Control)
Privacy Masking	3 Rectangular Zone
SD Card	Optional
Recording Mode	NVR/NAS/CMS/Web
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian

Package content

- 1 MDX-5030-B camera
- Installation manual and CD

Main Features

- 1/1.8" SONY Starvis Back-illuminated CMOS Sensor.
- H.264/H.265 Compression Method.
- 3.6mm Fixed Lens.
- IR Distance 20m Max.
- SD Card (optional)



Network

Ethernet Protocol	RJ-45 (10/100Base-T) TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, SMTP
ONVIF	Support ONVIF 2.4
P2P	YES, Support QR Code
POE	Optional, Support IEEE 802.3af
WIFI	N/A
Main Stream	2592*1944@20fps, 2048*1520@30fps
Sub Stream	720*480@30fps
IE Brower	IE8-11, Chrome
Smart Phone	iPhone, iPad, Android, Android Pad

General

Housing	Metal (IP65)
Anti-cut Bracket	No
IR Cut Filter	Yes
Operation Temperature	-20°C ~ +60°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%, 850 mA
Dimension	Ç 94.5 x 76(H) mm
Weight	450g