

NVR-XP3004

**4 CHANNELS IP CAMERAS,
NVR 1 BAY, P2P,
ONVIF 2.4**

Technical Specifications

System

Main Processor	ARM Cortex A9 Processor(HI3520D)
Operating System	Embedded LINUX

Video

Input	4 Channel, Support 1920×1080, 1280×960, 1280×720
Output	1 VGA, 1 HDMI

Alarm

Sensor Input	NO
Output	NO
Motion Detection	4 Channel, MD Zones: 396 (22 × 18)
Email Alarm	Support
Trigger Events	Recording, Email, FTP, Snapshot, Buzzer and Screen Tips

Display

VGA	Resolution: 1920 × 1080P /60Hz, 1280 × 1024 /60Hz, 1280 × 720 /60Hz, 1024 × 768 /60Hz
HDMI	resolution: 1920 × 1080P /60Hz, 1280 × 1024 /60Hz, 1280 × 720 /60Hz, 1024 × 768 /60Hz
Display Split	4 Channel / 1 Channel / 4 Channel / 1Channel
Digital Zoom	YES
OSD	Camera title, Time, Video loss, Recording, Motion Detection

Recording

Video Compression	H.264
Resolution	1080P(1920×1080) / 960P(1280×960) / 720P(1280×720) / D1 (704×576/704×480)
Record Rate	PAL :1080P@100fps, 960P@100fps, 720P@100fps, D1@100fps NTSC:1080P@120fps, 960P@120fps 720P@120fps, D1@120fps
Record Mode	Timer/ Motion Detection/ Manual
Storage	1 SATA up to 6GB

Package content

- 1 NVR-XP3004
- Installation manual and CD

Main Features

- HDMI, VGA, RJ-45, 2X USB.
- Support Onvif 2.4
- 4 Channels 1080P NVR
- Motion detection_4 Channels
- Output: 1VGA, 1 HDMI
- 1920*1080



ONVIF 2.4



FULL HD VIDEO



VIA BROWSER ACCESS



MOTION DETECTION



H.264 COMPRESSION



HTTP ACCESS

Playback & Backup

Local Sync Playback	1CH 1080P@30fps, 1CH 960P@30fps, 1CH 720P@30fps
Remote Sync Playback	YES
Search Mode	ALL, Channel, Time, Date, Motion Detection
Playback Functions	Play, Pause, Stop, Rewind, Fast play, Slow play
Backup Mode	USB Device /Network

Network

Interface	1 RJ45 10M/100M/1000M Adaptive Ethernet Interface
Network Functions	HTTP, IPv4, TCP/IP, DNS, DHCP, NTP, DDNS
Onvif Version	Support Onvif 2.4
Web Browser	IE8-11, Firefox, Google Chrome
CMS Software	Support Windows XP /Windows Vista /Windows7/Windows 8 /10
Cloud Support(P2P)	Yes
Smart Phone	iPhone, iPad, Android, Android PAD

General

Language	Chinese , English, Polish, Czech, Russian, Thai , Hebrew , Arabic , Bulgarian , Farsi, German , French , Portuguese , Turkic , Spanish , Italian , Hungarian , Romanian
USB Interface	2 USB 2.0 Interfaces
Power Supply	DC12V/3A
Working temperature	-10~55°/10~90%
Dimension(W×D×H)	219*217*43mm
Weight	2.0KG (without HDD)