

# NVR-XP9832

**32 CHANNELS IP CAMERAS,  
NVR 8 BAY ( MAX 6TB  
PER BAY), ONVIF 2.4**

## Technical Specifications

### System

<b>Main Processor</b>	Hi3535
<b>Operating System</b>	Embedded Linux

### Interface

<b>Operator interface</b>	16-bit true color graphic menu operation interface, support mouse operation
<b>Preview</b>	1/4/8/16/24/32

### Audio & Video

<b>Standard</b>	Video: PAL, NTSC
<b>Decode</b>	H.264
<b>Playback quality</b>	5M/3M/1080P/960P
<b>Monitor quality</b>	Max 1920*1080
<b>Video input</b>	8*5M/16*3/24*1080P/32*960P
<b>Motion detection</b>	Depend on camera
<b>Intercom</b>	Support

### Recording & Backup

<b>Record Mode</b>	Manual>Alarm>Dynamic Detection>TimingDetection>Timing
<b>Search mode</b>	Ssearch by time/ calendar/ event/ channel
<b>Record storage</b>	HDD, network
<b>Backup Mode</b>	Network backup, USB hard disk, USB burner, SATA burner

### Package content

- 1 NVR-XP9832
- Installation manual and CD

## Main Features

- HDMI, VGA, RJ-45, 2X USB.
- Support Onvif 2.4
- 32 Channels 1080P NVR
- Motion detection: 24 Channels
- Output: 1VGA, 1 HDMI



## External Interface

<b>Video I/O</b>	1ch RJ45/ 1ch VGA, 1ch HDMI
<b>Loop vout</b>	Unsupport
<b>Audio I/O</b>	1/1
<b>Alarm I/O</b>	16/4
<b>Network interface</b>	1*RJ45 10M/100M/1000M, Adaptive Ethernet Port
<b>USB</b>	2* USB2.0 ports
<b>PTZ Control</b>	1*RS485, 1*RS232 Support kinds of PTZ Protocols
<b>HDD</b>	8* SATA (Max 6 for each), 1*ESATA

## General

<b>ONVIF</b>	Support
<b>GB28181</b>	Optional
<b>Humidity</b>	0°C~+55°C, 10°C~90%RH
<b>Weight</b>	70mm×63.2mm×149.5mm
<b>Power Supply</b>	ATX power supply
<b>Dimension</b>	443mm(L)* 427.5mm(W) 92mm(H)