

OL-BU2080-BH

Cámara de Seguridad

OL-BU2080-BH Cámara Bullet



1/2.8" CMOS



Wide Dinamic Range



Visión Nocturna



Optical Zoom



4X1 Híbrida 4 IN 1



IP66

Características Principales:

- Resolución 1920 x 1080
- Sensor Pixart de 1 / 2.8" CMOS de 2MP
- AHD / CVI / TVI / CVBS 4 EN 1
- Lente fija de 2.8 mm
- IR máx. Distancia 40m
- Soporte de IP66 para exteriores, OSD y UTC

Image sensor	1/2.7" 2MP CMOS Sensor
Image resolution	2MP 1080P/ 960H
Effective pixels	1920(H)×1080(V)
TV system	PAL/NTSC
Electronic shutter time	1/25s~1/50,000s , 1/30s~1/60,000s
Scan system	Progressive
Usable illumination	0.01Lux/F2.0
S/N Ratio	≥50dB
Lens	Protection agains overload with 3sec loop cut
Focus length	2.8mm
Focus control	Fixed
Lens type	Fixed
Pixels	2MP
Autoiris	NO
Night vision	
IR LED	42μ x 2PCS
Infrared distance	40M
IR status	Under 10 Lux By CDS
Power On IR	CDS Auto Control
Dip switch	Opcional
Camera Features	
Day/night	Yes
Starlight	NO
Language menu	OSD
White balance	Auto/Manual
Control de ganancia	AUTO
Noise reduction	DNR
Image adjust	AUTO
WDR	AUTO
OSD	AUTO
UTC	AUTO
Dip Switch	Optional

OL-BU2080-BH

Cámara de Seguridad

OL-BU2080-BH Cámara Bullet



1/2.7"
CMOS



Wide Dinamic
Range



Visión
Nocturna



Optical
Zoom



4X1
Híbrida
4 IN 1



IP66

Características Principales:

- Resolución 1920 x 1080
- Sensor Pixart de 1 / 2.7 "CMOS de 2MP
- AHD / CVI / TVI / CVBS 4 EN 1
- Lente fija de 2.8 mm
- IR máx. Distancia 40m
- Soporte de IP66 para exteriores, OSD y UTC

General	
Housing	Metal, IP66
Bracket	YES
Dual Voltage	Optional
IR Cut Filter	YES
Heater	Optional
Audio	Optional
Operation Temperature	-10°C ~ +50°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%, 700mA
Dimension	200(W) x 171(H) x 83(D)mm
Weight	1.4 kg