

OL-MB1080-BH

Cámara de Seguridad

OL-MB1080-BH Cámara Bullet



1/2.7"
CMOS



Wide Dinamic
Range



Visión
Nocturna



Optical
Zoom



4X1
Híbrida
4 IN 1



IP66

Características Principales:

- Resolución 1920 x 1080
- Sensor Pixart de 1 / 2.7" CMOS de 2MP
- AHD / CVI / TVI / CVBS 4 EN 1
- Lente fija de 2.8 mm
- IR máx. Distancia 30m
- Soporte de IP66 para exteriores, OSD y UTC

Image sensor	1/2.7" 2MP CMOS Sensor
Image resolution	2MP 1080P/ 960H
Effective pixels	1920(H)×1080(V)
TV system	PAL/NTSC
Electronic shutter time	1/25s~1/50,000s , 1/30s~1/60,000s
Scan system	Progressive
Usable illumination	0.01Lux/F2.0
S/N Ratio	≥50dB
Lens	
Focus length	2.8mm/6mm
Focus control	Fixed
Lens type	Fixed
Pixels	3MP
Autoiris	NO
Night vision	10 AMP, Com NC NO
IR LED	ø5X42PCS
Infrared distance	30M
IR status	Less than 10 Lux By CDS
Power On IR	CDS Auto Control
Dip switch	Opcional
Camera Features	
Day/night	Auto/color/B&W
Starlight	NO
Language menu	OSD
White balance	Auto/Manual
Control de ganancia	AUTO
Noise reduction	NDR
Image adjust	AUTO
WDR	AUTO
OSD	AUTO
UTC	AUTO

OL-MB1080-BH

Cámara de Seguridad

OL-MB1080-BH Cámara Bullet



1/2.7"
CMOS



Wide Dinamic
Range



Visión
Nocturna



Optical
Zoom



4X1
Híbrida
4 IN 1



IP66

Características Principales:

- Resolución 1920 x 1080
- Sensor Pixart de 1 / 2.7" CMOS de 2MP
- AHD / CVI / TVI / CVBS 4 EN 1
- Lente fija de 2.8 mm
- IR máx. Distancia 30m
- Soporte de IP66 para exteriores, OSD y UTC

General	
Weatherproof	Metal
Bracket	YES
Heater	NO
Audio	Optional
Voltaje	Dual
IR cut filter	YES
Power supply	DC12V±10%, 550Ma
Working temperature	-10°C~ +50°C cRH95% Max
Storage temperature	-20°C~ +60°C RH95% Max
Dimensions	ø94.5 x 76(H) mm
Weight	650gr