OL-MB5020-BH
Cámara de Seguridad
OL-MB5020-BH Cámara Bullet

1/2.7" CMOS
Wide Dinamic Range
Visión Nocturna
Optical Zoom
4X1 Híbrida 4 IN 1
IP66

Características Principales:

- Resolución 1920 x 1080
- Sensor Pixart de 1 / 2.7 "CMOS de 2MP
- AHD / CVI / TVI / CVBS 4 EN 1
- Lente fija de 2.8 mm
- IR máx. Distancia 30m
- Soporte de IP66 para exteriores, OSD y UTC

Image sensor	1/2.7" 5MP CMOS Sensor
Image resolution	2MP 1080P/ 960H
Effective pixels	1920(H)×1080(V)
TV system	PAL/NTSC
Electronic shutter time	1/25s~1/50,000s , 1/30s~1/60,000s
Scan system	Progressive
Usable illumination	0.01Lux/F2.0
S/N Ratio	≥50dB
Lens	
Focus length	2.8mm/6mm
Focus control	Fixed
Lens type	Board Lens
Pixels	3MP
Autoiris	NO
Night vision	
IR LED	¢5X42PCS
Infrared distance	30M
IR status	Less than 10 Lux By CDS
Power On IR	CDS Auto Control
Dip switch	Opcional
Camera Features	
Day/night	Auto/color/B&W
Starlight	NO
Language menu	OSD
White balance	Auto/Manual
Control de ganancia	AUTO
Noise reduction	NDR
Image adjust	AUTO
WDR	AUTO
OSD	AUTO
UTC	AUTO

OL-MB5020-BH
Cámara de Seguridad
OL-MB5020-BH Cámara Bullet

1/2.7" CMOS
Wide Dinamic Range
Visión Nocturna
Optical Zoom
Hibrida 4 IN 1
IP66

Características Principales:

- Resolución 1920 x 1080
- Sensor Pixart de 1 / 2.7 "CMOS de 2MP
- AHD / CVI / TVI / CVBS 4 EN 1
- Lente fija de 2.8 mm
- IR máx. Distancia 30m
- Soporte de IP66 para exteriores, OSD y UTC

General	
Wheatherproof	Metal, IP66
Bracket	YES
Heater	NO
Audio	Optional
Voltaje	Dual
IR cut filter	YES
Power supply	DC12V±10%, 550Ma
Working temperature	-10ºC~ +50ºC cRH95% Max
Storage temperature	-20ºC~ +60ºC RH95% Max
Dimensions	¢94.5 x 76(H) mm
Weight	650gr