



## OLC-ML280

### ELECTROMAGNETIC DOOR LOCK

### MAIN FEATURES

- Fast and simple installation.
- Ideal for a single door.
- Fast and simple installation.
- Retention strength until 280 kg per door (600LB).
- Dual voltage 12V and 24 V with very low consumption.
- Anodized aluminium with aesthetic finish.
- Security cap screws that prevent the separation between the magnet and the support

### PACKAGING CONTENT

- 1 Electromagnetic lock door ML-280

### Technical Specifications

<b>Control LED</b>	Red
<b>Force support</b>	280 Kg/600LB
<b>Size</b>	218 mm(L) x 35mm(W) x 30mm(D)
<b>Input voltage</b>	12vDC o 24vDC
<b>Low current consumption</b>	12vDC 440mA , 24vDC 220mA
<b>EW Sensor</b>	No
<b>Secondary surface for mounting</b>	Yes
<b>Residual magnetism</b>	NO
<b>Terminal coverage system</b>	Yes
<b>Included</b>	All mounting accessories, simple plate, standard screws, user manual y Demag Residual Diode
<b>Power supply</b>	no included
<b>NOT included accessories</b>	L & Z brackets Glass door bracket
<b>Guarantee</b>	1 year
<b>Made in</b>	China