



OLC-SA737

ACCESS CONTROL

MAIN FEATURES

- Use User Management card to Programming, Easy Operation (Optional Remote control)
- Large capacity, Can support 15,000 Users.
- Metal shell with IP65 waterproof protection, can use outdoor
- Adopt function steady card reader of blocks
- Optional RS485 communication, Can real-time management user card and check records

PACKAGING CONTENT

- 1 OLC-SA737 access control
- Wall support
- Manual
- Installation CD
- 1x subjection ubication map
- 2x subjections systems

Technical Specifications

Working frequency	125khz or 13.56mhz
User capacity	15,000 users
Standard interface	Wiegand26 input, Optional RS485
Work Voltage	DC 12V±10%
Dry contact output	Relay ,simple inverter, COM NC NO
Operating current	< 100mA
Reading Range	1~15cm
RFID identification time	Less than 0,1s
Administration Software	No license
SDK	Free and compatible(VB, C++, C#, Delphi, KSDK y ODM)
Waterproof degree	IP65 rating
Ambient Temperature	0~60 Degree
Ambient Humidity	20%~80%
FRR	<=1%.
FAR	<=0.0001%.
Software OS	XP/Win2003/Vista/Win7/Win8 (32bit / 64bit)
Electricity lock output	≤3A
Output short circuit protection time	≤100μS
Open time	0 ~ 99 seconds (adjustable)
Peso	0.095 Kg
Size	128(L) x 85(W) x 22(H) mm
Guarantee	1 Year
Made in	China