

OLC-TC900

Control de Acceso

OLI-TC900 Control de Acceso



Keyboard



Biometric



SDK



RFID



Wiegand



IP65



USB port



Door bell



Relay



Alarm

Características Principales:

- Admite entrada de cámara IP H.265 / H.264 de forma adaptativa
- Access control and High standards security protocols personnel control.
- For control in offices, factories, schools, etc.
- Smart personnel control with basic Excel reports.
- 600dpi RFID fingerprints sensor with high energy save function, for alternative feed systems.
- Easy to start with 3 steps for fingerprint record (Max time rate: 8 s per person).
- IP work together system: Easy installation for multiple devices and launch a unique report of all of them.
- TFT 2,4 inches screen, full color.
- Flash USB port for emergency downloads reports + TCP-IP interface + USB communication.
- Multiples Bio/RFID lecture systems with combinations: fingerprint / card / password / fingerprint + card / Card + Password + fingerprint / Fingerprint + Password / Card + Password.
- Advanced functions with Access control: anti-pass-back, electric lock door interface, door sensor, exit button, alarm and doorbell.
- Auxiliar input for smoke detector or emergency switches
- Visual indications for the allowance or declination of fingerprints.
- Olex controls has Chinese Police Product Approbation, CE and FCC Certificated.

LCD Screen	2.4 inch TFT (320x 240 Color Screen)
Voltaje de corriente	DDC 12V / 1.5 AMPC 12V / 1.5 AMP
Wiegand	26/34 input/output
Entada de contacto seco	two Relay ,simple inverter,COM NC NO
Ati-passback function	YES
Amenaza de alarma	anti-dismantling alarm.
Sensor	Opening door sensor, by push button, by remote opening, opened door, entry and exit alarm Entrada de auxiliar 1 (for linking)
Operation temperatura	0°C - 50°C
Tamaño del terminal	181 x 91 x 36mm
Fingerprint sensor Resolución:	600 ppp (dpi)
Sistema operativo	REALANDRZDC2911
Users capacity	2000 users
Capacidad de tarjetas RFID	2000 cards
Total records capacity	100000 Comunicación TCP / IP, USB memory, RS485USB, RS485
Autenticación method	Fingerprints/RFID (125Khz)/Contraseña
Tipo de tarjeta de proximidad	Tarjetas RFID para el estándar, ID de modelo:EM o compatible
BIO identification time	less than 0,5seg
Tiempo de identificación RFID	less than 0,1seg
Audio language	english, spanish
Idioma de texto	english, spanish
Administration software	Non license SDK
free compatible (VB, C++, C#, Delphi, KSDK y ODM)	
Autonomus functioning	50.000 records
FRR	<=1%
FAR	<=0.0001%
Distancia detector de tarjetas	5-15mm
Software OS	XP/Win2003/Vista/Win7/Win8 (32bit / 64bit)
Tamaño del paquete	246 x 164 x 71 mm
Terminal weighth	0.48kg
Peso del paquete	0.812kg
Guarantee	1 year
Origen	China