

OLI-CBR2000

Starlight IP camera

OLI-CBR2002 2 Megapixels
OLI-CBR2005 5 Megapixels
OLI-CBR2008 8 Megapixels



Características Principales:

- Codificación H.265. Soporte dual-stream
- Admite configuración WEB, software de gestión remota para cliente de PC, aplicación móvil, proporciona el archivo SDK
- Protocolo RTSP y Onvif compatible con muchos NVR de terceros
- Admite la función de fuente de alimentación interna PoE (opcional)
- Zoom óptico 4X, enfoque más rápido, la imagen es clara durante el zoom
- Lente con zoom motorizado de 2.8-12 mm, acercar y alejar mediante control remoto PTZ

Model	OLI-CBR2002	OLI-CBR2005	OLI-CBR2005	OLI-CBR2008
Image Sensor	SC2235 1/2.T' CMOS	SC5235 1/2.T' CMOS	OS05A10 1/2.T' CMOS	Sony274 1/2.T' CMOS
Main Processor	MSC313E	MSC316DM	Hi3516A	Hi3516AV200
Effective Pixels	2.0MP	5.0MP	5.0MP	8.0MP
Resolution	"1920(H)"*1080(V)"	"2592(H)"*1944(V)"	"2592(H)"*1944(V)"	"3840(H)"*2160(V)"
Scanning System	Progressive Scanning	Progressive Scanning	Progressive Scanning	Progressive Scanning
Video Compression	H.265+/H.265/H.264	H.265+/H.265/H.264	H.265+/H.265/H.264	H.265+/H.265/H.264
Main Stream	1080P@20fps	5MP@15fps	5MP@25fps	8MP@20fps
Sub Stream	"640"*480@30fps"	"640"*480@30fps"	"704"*576@30fps"	"704"*576@30fps"
BPS	32kb-8Mbps	32kb-8Mbps	32KB-16Mbps	32kb-16Mbps
LENS				
Focus Length	4x optical zoom Motorized 2.8-12mm	4x optical zoom Motorized 2.8-12mm	5x optical zoom motorized lens	3x optical zoom motorized lens
Focus control	Electronic Auto Focusing			
lens pixels	Foctek 3MP	YTOT 5MP	YTOT 6MP	YTOT 8MP
Video color	Full color/B&W/Auto (time detection/IR CUT Switch)			
Infrared LEO	24pcs SMT IR LEO			
Infrared Distance	25-35m			
IR Status	Under 10 Lux by CDS			
IR Power On	CDS Auto Control			
Audio (OPTION)				
AudioIN/OUT	1ch audio			
Compression rate	4.75Kbps-12.2Kbps			
NETWORK				
Ethernet	RJ45 (10/100Base-I)			
Protocol	TCP/IP,DH-CP,HTTP,HTIPS NT-P,DNS,RTP,RTSP"			
ONVIF	Support ONVIF			
P2P	Support			
IE Brower	IE7-11,Google Chrome,Firefox"			
Smart Phone	iPhone,iPad,Android,Android Pad"			

OLI-CBR2000

Starlight IP camera

OLI-CBR2002 2 Megapixels
 OLI-CBR2005 5 Megapixels
 OLI-CBR2008 8 Megapixels



CAMERA FEATURES

SNR	>50dB (AGC on)
WDR	Digital WDR
DNR	30
Minimum illumination	color :0.001 ux/F1.2 (AGC on);B&W:0 Lux (IR on)
	trast, Saturation, AWB,AGC,AE,Privacy Mask,Mirror,Flip,BLC,FLK,motion detection"
language	Chinese Simplified,English

General

Operation Temperature	-30 c-60 c
Storage Temperature	0 c-40 c
Power Source	12 VDC ± 10%,PoE (802.3af Class3)"
Material	Metal,IP66 waterproof"
Dimension	Camera:275(W)x9(D) x 12(H)cm Package:26.4""17.4""15.3 cm"
Weight	0.9kg