

## OLI-CBV2002 Varifocal IP camera

OLI-CDV2002 2 Megapixels

OLI-CDV2004 4 Megapixels

OLI-CDV2005 5 Megapixels



### Características Principales:

- Codificación H.265. Soporte dual-stream
- Admite configuración WEB, software de gestión remota para cliente de PC, aplicación móvil, proporciona el archivo SDK
- Lente varifocal 2.8-12 mm, ángulo de visión de 115° ~ 25°
- 24 \* 14μ SMD IR LED, larga vida, distancia IR de hasta 30-35 metros
- Admite la función de fuente de alimentación interna PoE (opcional)
- Carcasa sólida de aluminio, resistente al agua IP67. Soporte de 3 ejes.

Model No:	OLI-CVD2002	OLI-CVD2002	OLI-CVD2004	OLI-CVD2005
<b>Resolution</b>	1920(H)*1080(V) 2MP	1920(H)*1080(V) 2MP	2588(H)*1520(V) 4MP	2592(H)*1944(V) 5MP
<b>Image Sensor</b>	1/2.7" SC2235	1/2.9" SONY323	1/3" OV4689	1/3"SC5035
<b>Main processor</b>	Mstar MSC313E	Mstar MSC313E	Mstar MSC316DM	Mstar MSC316DM
<b>Main Stream</b>	1920*1080@20fps	1920*1080@20fps	2688*1520@20ps	2592*1944@15fps
<b>Sub Stream</b>	640*480	640*480	640*480	720*480
<b>Video Compression</b>	H.265/H.264			
<b>BPS</b>	32Kbps~3.5Mbps	32Kbps~3.5Mbps	32Kbps~5Mbps	64Kbps~8Mbps
<b>LENS</b>				
<b>Focus Length</b>	2.8-12mm			
<b>Lens control</b>	Varifocal			
<b>Lens pixels</b>	3MP	3MP	4MP	5MP
<b>NIGHT VISION</b>				
<b>Video color</b>	Full color/B&W/ Auto	Full color/B&W/ Auto	Full color/B&W/ Auto	Full color/B&W/ Auto
<b>Infrared LED</b>	Yes. 14μ SMT infra red LED*24			
<b>Infrared Distance</b>	30-35m			
<b>IR Status</b>	Under 10 Lux By CDS			
<b>IR Power On</b>	CDS Auto Control			
<b>Audio ( OPTION)</b>				
<b>Audio IN/OUT</b>	Optional			
<b>Encoding format</b>	AMR,G711			
<b>Compression rate</b>	4.75Kbps-12.2Kbps			
<b>NETWORK</b>				
<b>Ethernet</b>	RJ-45 (10/100Base-T)			
<b>Protocol</b>	HTTP/RTSP/FTP/ PPPOE/DHCP/ NTP/ONVIF/P2P etc, support Hikvi- sion private proto- col			
<b>ONVIF</b>	Support ONVIF 2.6			
<b>P2P</b>	Support			
<b>IE Brower</b>	IE7-11, Google Chrome, Firefox, Support CMS, PC client preview & playback, P2P remote view, sup- port cloud, pro- vide SDK file			
<b>Smart Phone</b>	iPhone, iPad, An- droid, Android Pad			

## OLI-CBV2002 Varifocal IP camera

OLI-CDV2002 2 Megapixels

OLI-CDV2004 4 Megapixels

OLI-CDV2005 5 Megapixels



<b>Smart Phone</b>	iPhone, iPad, Android, Android Pad			
<b>CAMERA FEATURES</b>				
<b>Day/Night</b>	Full color/B&W/Auto	Full color	Full color/B&W/Auto	Full color/B&W/Auto
<b>SNR</b>	>50dB (AGC off)			
<b>WDR</b>	>80dB	>80dB	>80dB	>80dB
<b>DNR</b>	3D			
<b>Minimum illumination</b>	color: 0.01 Lux@F1.2	color: 0.01 Lux@F1.2	color: 0.01Lux@F1.2	color: 0.01Lux@F1.2
<b>Recording Mode</b>	NVR/NAS/CMS/Web			
<b>Language</b>	Chinese Simplified, English			
<b>GERNERAL</b>				
<b>Housing</b>	Metal, IP67 water-proof			
<b>Bracket</b>	3Aixs			
<b>Operation Temperature</b>	-30 ~60			
<b>Storage Temperature</b>	0 ~40			
<b>Power Source</b>	12 VDC ± 10%, PoE (802.3af Class3)			
<b>Dimension</b>	Camera:275(W)*90(D)*120(H)mm Package: 264*174*153 mm			
<b>Weight</b>	900g			