

# OLI-CD3000

## Starlight IP Dome camera

OLI-CDR3002 2 Megapixels

OLI-CDR3005 5 Megapixels



### Características Principales:

- Codificación H.265. Soporte dual-stream
- Admite configuración WEB, software de gestión remota para cliente de PC, aplicación móvil, proporciona el archivo SDK
- Protocolo RTSP y Onvif compatible con muchos NVR de terceros
- Admite la función de fuente de alimentación interna PoE (opcional)
- Análisis inteligente: detección de cruce de línea, conteo de objetivos, detección de área, detección de objetos perdidos / izquierda

Model Number	OLI-CD3002	OLI-CD3002	OLI-CD3005
Image Sensor	SC2235 1/2.1" CMOS	"Sony323 1/2.8" CMOS"	SC5235 1/2.1" CMOS
Main Processor	MSC313E		MSC316DM
Effective Pixels	2.0MP		5.0MP
Resolution	"1920(H)"*1080M"	"1920(H)"*1080M"	"2560(H)"*1920M"
Scanning System	Progressive Scanning		
Video Compression	H.265+/H.264		
Main Stream	1080P@20fps	1080P@20fps	5MP@15fps/4MP@20fps
Sub Steam	"640"*480@30fps"		
BPS	32kb-8Mbps	32kb-8Mbps	32kb-8Mbps
<b>LENS</b>			
Focus Length	2.8mm/3.6mm/6m-m/8mm		
Focus control	fixed		
Lens pixels	3MP		5mP
<b>NIGHT VISION</b>			
Infrared LEO	18pcs SMT IR LEO		
Video color	Fullcolor/B&W/Auto (time detection/IR/CUT Switch)		
IR Status	Under 10 Lux by CDS		
IR Power On	CDS Auto Control		
IR distance	20-25m		
<b>Audio ( OPTION)</b>			
AudiIoN/OUT	1ch audio		
Encoding Format	AMR,G711A		
Compression rate	4.75Kbps-12.2Kbps		
<b>CAMERA FEATURES</b>			
SNR	>50dB (AGC on)		
WDR	Digital WDR		
DNR	30		
Minimum illumination	color :0.001Lux/F1.2 (AGC on);B&W:0 Lux (IR on)		
Language	Chinese Simplified,English		
Image setting	Brightness, Contrast, Saturation,AWB,AG-C,AE,Privacy Mask,Mirror,Flip,BLC,FLK,motion detection"		

# OLI-CD3000

## Starlight IP Dome camera

OLI-CDR3002 2 Megapixels

OLI-CDR3005 5 Megapixels



NETWORK	
<b>Ethernet</b>	RJ45 (10/100Base-I)
<b>Protocol</b>	TCP/IP,DHCP,HTIP,HTIPS NTP,DNS,RTP RTSP"
<b>ONVIF</b>	Support ONVIF
<b>P2P</b>	Support
<b>IE Brower</b>	IE?-11,Google Chrome,- Firefox"
<b>Smart Phone</b>	iPhone,iPad,Android,An- droid Pad"
<b>Alarm push</b>	FTP,Email,mobile ap- p,CMS client"
GERNERAL	
<b>Operation Temperature</b>	-3o c-6o c
<b>Storage Temperature</b>	o c-4o c
<b>Power Source</b>	12 VDC ± 10%,PoE (802.3af Class3)
<b>Material</b>	Metal,IP66 waterproof"
<b>Dimension</b>	Camera:<D9.5x6.5cm "Package:12.5**12.5**9.5 cm"
<b>Weight</b>	0.28kg