

# OLI-CDV3000

## Varifocal IP camera

OLI-CDV3002 2 Megapixels  
 OLI-CDV3004 4 Megapixels  
 OLI-CDV3005 5 Megapixels



### Características Principales:

- Codificación H.265. Soporte dual-stream
- Admite configuración WEB, software de gestión remota para cliente de PC, aplicación móvil, proporciona el archivo SDK
- Lente varifocal 2.8-12 mm, ángulo de visión de 115° ~ 25°
- 24 \* Φ5 LED infrarrojo, larga vida, distancia IR de hasta 25 metros
- Admite la función de fuente de alimentación interna PoE (opcional)
- Carcasa sólida de aluminio, resistente al agua IP66.

|                          |   |                         |                         |                         |
|--------------------------|---|-------------------------|-------------------------|-------------------------|
| <b>Model No:</b>         | OLI-CDV3002   | OLI-CDV3002             | OLI-CDV3004             | OLI-CDV3005             |
| <b>Resolution</b>        | 1920(H)*1080(V) 2MP   | 1920(H)*1080(V) 2MP     | 2588(H)*1520(V) 4MP     | 2592(H)*1944(V) 5MP     |
| <b>Image Sensor</b>      | 1/2.7" SC2235   | 1/2.9" SONY323          | 1/3" OV4689             | 1/3"SC5035              |
| <b>Main processor</b>    | Mstar MSC313E   | Mstar MSC313E           | Mstar MSC316DM          | Mstar MSC316DM          |
| <b>Main Stream</b>       | 1920*1080@20fps   | 1920*1080@20fps         | 2688*1520@20ps          | 2592*1944@15fps         |
| <b>Sub Stream</b>        | 640*480   | 640*480                 | 640*480                 | 720*480                 |
| <b>Video Compression</b> | H.265/H.264   |                         |                         |                         |
| <b>BPS</b>               | 32Kbps~3.5Mbps  | 32Kbps~3.5Mbps          | 32Kbps~5Mbps            | 64Kbps~8Mbps            |
| <b>LENS</b>              |   |                         |                         |                         |
| <b>Focus Length</b>      | 2.8-12mm  |                         |                         |                         |
| <b>Lens control</b>      | Varifocal   |                         |                         |                         |
| <b>Lens pixels</b>       | 3MP   | 3MP                     | 4MP                     | 5MP                     |
| <b>NIGHT VISION</b>      |   |                         |                         |                         |
| <b>Video color</b>       | Full color/B&W/<br>Auto   | Full color/B&W/<br>Auto | Full color/B&W/<br>Auto | Full color/B&W/<br>Auto |
| <b>Infrared LED</b>      | Yes. Φ5 infrared LED*24   |                         |                         |                         |
| <b>Infrared Distance</b> | 30-35m  |                         |                         |                         |
| <b>IR Status</b>         | Under 10 Lux By CDS   |                         |                         |                         |
| <b>IR Power On</b>       | CDS Auto Control  |                         |                         |                         |
| <b>Audio ( OPTION)</b>   |   |                         |                         |                         |
| <b>Audio IN/OUT</b>      | Optional  |                         |                         |                         |
| <b>Encoding format</b>   | AMR,G711  |                         |                         |                         |
| <b>Compression rate</b>  | 4.75Kbps-12.2Kbps   |                         |                         |                         |
| <b>NETWORK</b>           |   |                         |                         |                         |
| <b>Ethernet</b>          | RJ-45 (10/100Base-T)  |                         |                         |                         |
| <b>Protocol</b>          | HTTP/RTSP/FTP/PPPOE/DHCP/NTP/ONVIF/P2P etc, support Hikvision private protocol  |                         |                         |                         |
| <b>ONVIF</b>             | Support ONVIF 2.6   |                         |                         |                         |
| <b>P2P</b>               | Support   |                         |                         |                         |
| <b>IE Brower</b>         | IE7-11, Google Chrome, Firefox, Support CMS, PC client preview & playback, P2P remote view, support cloud, provide SDK file |                         |                         |                         |
| <b>Smart Phone</b>       | iPhone, iPad, Android, Android Pad  |                         |                         |                         |

## OLI-CDV3000

### Varifocal IP camera

OLI-CDV3002 2 Megapixels

OLI-CDV3004 4 Megapixels

OLI-CDV3005 5 Megapixels



#### NETWORK

|                    |   |
|--------------------|---|
| <b>Ethernet</b>    | RJ45 (10/100Base-I)                         |
| <b>Protocol</b>    | TCP/IP,DHCP,HTIP,HTIPS<br>NTP,DNS,RTP RTSP" |
| <b>ONVIF</b>       | Support ONVIF                               |
| <b>P2P</b>         | Support                                     |
| <b>IE Brower</b>   | IE?-11,Google Chrome,-<br>Firefox"          |
| <b>Smart Phone</b> | iPhone,iPad,Android,An-<br>droid Pad"       |
| <b>Alarm push</b>  | FTP,Email,mobile ap-<br>p,CMS client"       |

#### GERNERAL

|                              |   |
|------------------------------|---|
| <b>Operation Temperature</b> | -30 c-60 c  |
| <b>Storage Temperature</b>   | 0 c-40 c  |
| <b>Power Source</b>          | 12 VDC ± 10%,PoE<br>(802.3af Class3)                  |
| <b>Material</b>              | Metal,IP66 waterproof"                                |
| <b>Dimension</b>             | Camera:<D9.5x6.5cm<br>"Package:12.5**12.5**9.5<br>cm" |
| <b>Weight</b>                | 0.28kg  |