

OLI-NV5000

Smart NVR

OLI-NV5128 128 canales



Características Principales:

- Admite acceso de video en tiempo real completo de 4/8 / 16ch 4k, 1U, 2 puertos SATA
- Admite flujo H.265 / H.264, funcionamiento integrado de Linux
- Soporte de reproducción de video, monitoreo remoto y respaldo.
- Admite vista previa y reproducción con amplificación electrónica 12 veces.
- Protocolo estándar ONVIF, RTSP, GB28181.
- Admite DDNS, EMAIL, UPNP, NTP, etc.
- Soporte web, monitoreo móvil, cliente de PC, software CMS.
- Soporte UMeye P2P.
- Soporte de agrupación de canales, ciclo de vista previa.
- Admite reproducción sincrona de video de 4/8 / 16ch sub stream y reproducción sincrona multicanal.
- Admite autenticación de doble contraseña.

Model	OLI-NV5128
Operating System	Embedded Linux operating system
Video	
Network video input	128ch 4K/5MP/3MP/1080p/960p/720p input
Network video output	2*VGA/2* HDMI,
Video bit rate	16-8000Kbps
Image preview	1/4/6/8/9/16/25/36/64 channel
Video compression	H.265/H.264/MJPEG
Capture mode	Schedule/Manual, JPEG format
Audio	
Audio	1ch audio input and 1ch output
Audio compression	G.711A
Storage	
HDD port	16 SATA ports, 2 E-SATA
Raid mode	Raid0, Raid1, Raid5, Raid6, Raid10
Capacity	Support 6TB HDD
Alarm	
Motion detection	Support image set to 396 (22*18) detection areas, multistage sensitivity
Smart detection	Motion detection, video miss, video occlusion, occlusion alarm
Alarm	16ch input, 8ch output
Network management	
Network protocol	TCP/IP,HTTP,DDNS,SMTP(SSL),DHCP,PPPOE,UPNP,NTP
Compliance protocol	ONVIF, RTSP, GB28181
Remote application	WEB(IE, Chrome, Firefox, Safari), IOS, Android Mobile monitor
Smart analysis	Target count, Item detection, Area detection, Virtual cordon, Scene transformation
Others	Dual password authentication

OLI-NV5000

Smart NVR

OLI-NV5128 128 canales



Video management

Record mode	Manual/Schedule record, Motion alarm record, Motion alarm Snap, link
down record	
Resolution	128ch 4K/5MP/3MP/1080p/960p/720p
Broadband access	640Mbps
Record frame rate	1-30fps
Video query	Time, Date, Event, Channel, Exact Search (accurate to second,
Record storage path	Local, Network, NAS, IPSAN
Playback&Backup	
Playback mode	Regular playback, instant replay, event playback, external file playback
	4ch 4K/5MP
Playback capability	9ch 3MP
	16ch 1080p/960p/720p
	Play, Stop, Rewind, Next File, Previous File, Next Camera, Previous
Playback operations	Camera, Fast play, Slow play, Single frame, Backup, Screenshot, Full screen selection
Backup mode	Removable HDD, USB flash disk, Network backup
External ports	
Network port	2 RJ45 Ports (100M/1000M Ethernet port)
USB port	2PCS 2.0 USB port, 1PCS 3.0 USB port
RS485 port	Support
Audio port	1PCS input, 2PCS output
General	
Power supply	AC100, 240V, 47Hz~63Hz
Power consumption	≤ 50W (Without HDD)
Storage condition	-10°C ~ 55°C / 10%-90%RH
Dimensions	W430mm×D483mm×H143mm
Peso	18.5KG