



H.265

PN-IPWP

**2MP MINIATURE IP,
H.264/H.265, WIFI,
PINHOLE LENS 3.7 MM**

Technical Specifications

Camera

Image sensor	IMX323
Resolution	1080P
Effective Pixels	1985(H)*1105(V)
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec
Reset Button	Optional
S/N Ratio	≥52dB
Scanning System	Progressive
Video Output	Network

Lens

Focus Length	3.7mm/F2.8 Taper Pin Hole
Focus Control	Fixed
Lens Type	Fixed
Pixels	2 mp

Night Vision

Infrared LED	/
Infrared Distance	/
IR Status	/
IR Power On	/

Camera Features

Day/Night	Color/ B&W (IR-CUT)
Compression	H.264/H.264+/H.265/JPEG/AVI
Image settings	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR, White Balance, BLC, FLK(Flicker Control)
Motion Detection	Support
Privacy Masking	3 Rectangular Zone
BLC	Support
Recording Mode	NVR/NAS/CMS/Web
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian

Package content

- 1 PIN-IPWP camera
- Installation manual and CD

Main Features

- 1/2.9" SONY Starvis CMOS Sensor
- H.264/H.265 Compression Method
- 3MP Taper Pinhole Lens 3.7mm
- WiFi (Max. 100m) is Optional

Network

Ethernet Protocol	RJ-45 (10/100Base-T) WIFI TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP, DNS,DDNS,RTSP,RTSP,RTCP,NTP,SMTP
ONVIF	Support ONVIF 2.4
P2P	YES, Support QR Code
POE	Optional, Support IEEE 802.3af
WIFI	Optional
Main Stream	1920*1080@30fps
Sub Stream	720*480@30fps
IE Brower	IE8-11, Firefox
Smart Phone	iPhone, iPad, Android, Android Pad
Audio	NO
SD Card Slot	Yes, Support Max 64GB (optional)

General

Housing	IP65
Anti-cut Bracket	No
IR Cut Filter	No
Operation Temperature	-20C~ +60C° RH95% Max
Storage Temperature	-20C ~ +60C RH95% Max
Power Source	DC12V±10%, 550mA
Dimension	36(W) x 36(H) x33(D)mm
Weight	300g