



H.265

SP-4030-IR-20X

10" OUTDOOR
HIGH SPEED, 20X, PTZ,
IR 100 M, ONVIF 2,4

Technical Specifications

Camera

Image sensor	HI3515D
Resolution	4 MP
Effective Pixels	2592(H)*1944(V)
TV System	PAL/NTSC
Electronic Shutter Time	PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec;
S/N Ratio	≥50dB
Scanning System	Progressive
Video Output	Network

Lens

Focus Length	4.7mm-94mm
Focus Control	20X Optical Zoom

Night Vision

Infrared LED	Ç 42 x 8PCS IR LEDS + 4PCS LED Laser
IR Range	120m
Auto Control IR LED	PWM

Camera Features

Day/Night	Color/B&W (IR-CUT)
WDR	Yes
Image settings	Saturation/Brightness/Contrast / Sharpness, Mirror, 3D NR , White Balance, BLC, FLK(Flicker Control)
Recording Mode	NVR/NAS/CMS/Web
Privacy Masking	3 Rectangular Zone

Network

Network protocol	TCP/IP, TTP, NTP, IGMP, DHCP, UDP, SMTP, RTP, RTSP, ARP, DDNS, DNS, PPPoE, P2P
ONVIF	Support- ONVIF 2.4
Main Stream	1920*1080@30fps
Sub Stream	720*480@30fps
Tri Stream	352*288@30fps
Ethernet	RJ-45 (10/100Base-T)
P2P	YES, Support QR Code
POE	Support IEEE 802.3af
Video Delay	0.3S (Within the Lan)
IE Brower	IE8-11, Chrome
Smart Phone	iPhone, iPad, Android, Android Pad

Main Features

- 1/3" SONY Low Illumination CMOS Sensor
- H.264/ H.265 Compression Method
- IR Distance 120m Max.
- IP66 Outdoor



PTZ

Horizontal Rotation Speed	200°/S
Horizontal Rotation Range	0°~360°
Tilt Rotation Speed	100°/s
Auto Flip	Support
Ratio Speed	Support
360° Scan	Support
A-B Scan	Support
Preset Points	220
Guard Tours	3 groups
Guard Points	Max.16 points

General

Weatherproof	IP66
Operating Temperature	Indoor: 0°~ +40° Outdoor: -40°~ +60°
Operating Humidity	≤90% Non Condensing
Heater & Blower	Auto temperature control
Power	DC12V/4A
Lightning Protection	Transient voltage 6000V
Dimension	33x33x52(cm)
Weight	6.1Kgs