



H.265

VDS-2030-VFIR-MX5

2MP OUTDOOR DOME, VANDAL PROOF, 5X P66, IR 30M, ONVIF, PoE

Technical Specifications

Camera

Image sensor	IMX323
Resolution	2MP 1080P
Effective Pixels	1985(H)*1105(V)
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec
Sync System	External
Usable Illumination	0.01Lux
S/N Ratio	≥52dB
Scanning System	Progressive
Video Output	Network

Lens

Focus Length	2.7-13.5mm 5X Motor Zoom Auto Focus Lens
Focus Control	Auto
Lens Type	Motorized
Pixels	3M Pixels

Night Vision

Infrared LED	14μ x 21PCS
Infrared Distance	30M
IR Status	Under 10 Lux By CDS
IR Power On	CDS Auto Control

Camera Features

Day/Night	Color/ B&W (IR-CUT)
Compression	H.264/H.265/JPEG/AVI/MJPEG
Image settings	Saturation/Brightness/Contrast/Sharpness, Mirror, 3D NR, White Balance, BLC, FLK(Flicker Control)
Motion Detection	Support
Privacy Masking	3 Rectangular Zone
SD Card	Optional
Audio	Optional
WDR	NO
Recording Mode	NVR/NAS/CMS/Web
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian

Package content

- 1 VDS-2030-VFIR-MX5 camera
- Installation manual and CD

Main Features

- 1/2.9"SONY Low Illumination CMOS Sensor
- H.264/H.265 Compression Method
- 2.7-13.5mm 5X Motor Zoom Auto Focus Lens
- IR Distance 30m Max.
- Vandal Proof



Network

Ethernet Protocol	RJ-45 (10/100Base-T) TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP, DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP Support ONVIF 2.4
ONVIF	Support ONVIF 2.4
P2P	YES, Support QR Code
POE	IEEE 802.3af
WIFI	N/A
Video Delay	0.3S (Within the Lan)
Main Stream	1920*1080@30fps
Sub Stream	720*480@30fps
IE Brower	IE8-11, Chrome
Smart Phone	iPhone, iPad, Android, Android Pad

General

Housing	Metal (Vandalproof - IP66) optional: for wall
Anti-cut Bracket	No
IR Cut Filter	Yes
Operation Temperature	-20C~ +60C° RH95% Max
Storage Temperature	-20C~ +60C° RH95% Max
Power Source	DC12V±10%, 700mA
Dimension	∅ 131 x 93(H) mm
Weight	800g