



SPECIFICATION

Model	N5018
Camera	
Image Sensor	1/2.9" SONY Low Illumination 2.1MP CMOS Sensor
Horizontal Resolution	2 MP
Compression	H.264/H.265
S/N Ratio	>50db
PTZ	
Horizontal Rotation Speed	200°/S
Horizontal Rotation Range	0°~360°
Tilt Rotation Speed	100°/s
Tilt Rotation Range	0°~90°
Auto Flip	Support
Ratio Speed	Support
360° Scan	Support
A-B Scan	Support
Preset Points	220
Guard Tours	3 groups
Guard Points	Max.16 points
Lens	
Focus Length	22X= 3.9 mm-85.5mm

Focus Control	22X Optical Zoom
Night Vision	
Infrared LED	Φ 42 x 8PCS IR LEDS + 4PCS LED Laser
IR Range	200m
Auto Control IR LED	PWM
Network	
Network protocol	TCP/IP , TTP , NTP , IGMP , DHCP , UDP , SMTP , RTP , RTSP , ARP , DDNS , DNS , PPPoE , P2P
ONVIF	Support
Network interface	Built-in RJ45 network interface,support 10M/100M IP DATA
Interface	
Audio	/
Alarm	/
General	
Weatherproof	IP67
Operating Temperature	Indoor: 0°~ +40° Outdoor: -40°~ +60°
Operating Humidity	≤90% Non Condensing
Heater & Blower	Auto temperature control
Power	DC12V/4A
Lightning Protection	Transient voltage 6000V
Dimension	33x33x52(cm)
Weight	6.1Kgs

